

QNVB.MH29445 - Lead Content Verification of Products in Contact with Potable Water

Lead Content Verification of Products in Contact with Potable Water

[See General Information for Lead Content Verification of Products in Contact with Potable Water](#)

AALBERTS INTEGRATED PIPING SYSTEMS APAC INC

MH29445

295 SEC 3 WANDAN RD
WANDAN TOWNSHIP
PINGTUNG HSIEN, 913 TAIWAN

Trademark and/or Tradename: "SHURJOINT" , **SHURJOINT**

Bronze Fittings, Model(s) C10 90 degree Elbow, C11 45 degree Elbow, C20 Tee, C21 Reducing Tee (GR x GR x GR), C26 Reducing Tee (GR x GR x CUP), C50 Concentric Reducer (GR x GR), C52 Concentric Reducer (GR x CUP), C55 Transition Adapter, C60 Cap

Butterfly Valve, Model(s) SJ-300N - Sizes 2" - 24", SJ-400# - Sizes 2" - 8", SJ-C300 - Sizes 2" - 6"

Coupling, Model(s) C307 Transition Coupling"(2"-6") (t)

Dielectric Fittings, Model(s) DE30-GG Dielectric Fittings, 2" - 8"

EPDM Gaskets, Model(s) Fast-Fit Grade E-pw EPDM Gasket (3/4" - 8") (A), Grade E-pw EPDM Flange Gasket (2" - 24") (A)

EPDM Gaskets, Model(s) Grade E-pw EPDM Flange Gasket (for copper tubings) (2" - 8") (A)

EPDM Gaskets, Model(s) Grade E-pw EPDM GapSeal Gasket (1-1/4" - 24") (A)

EPDM Gaskets, Model(s) Grade E-pw EPDM GapSeal Gasket (for copper tubings) (2" - 8") (A)

EPDM Gaskets, Model(s) Grade E-pw EPDM Mechanical Tee Gasket (2-1/2" x 1/2" - 4" x 1-1/4")

EPDM Gaskets, Model(s) Grade E-pw EPDM Reducing Gasket (2" x 1-1/2" - 8"x6") (A)

EPDM Gaskets, Model(s) Grade E-pw EPDM Standard Gasket (3/4" - 24") (A), Grade E-pw EPDM Transition Gasket 2" - 4"

Halogenated Butyl Gaskets, Model(s) Grade M Halogenated Butyl Flange Gasket (3"-24"), Grade M Halogenated Butyl GapSeal Gasket (3"-24")

Halogenated Butyl Gaskets, Model(s) Grade M Halogenated Butyl Transition Gasket (3"-12")

SS grooved end fitting, Model(s) SS-10 90 degree Elbow size 1" - 12", SS-11 45 degree Elbow size 1" - 12", SS-20 Tee size 1" - 12", SS-21 Reducing Tee size 10" - 24", SS-21F Reducing Tee size 10" - 24", SS-50 Concentric Reducer size 10" - 24", SS-50F Concentric Reducer size 10" - 24", SS-60 Cap size 1" - 12"

SS grooved fitting, Model(s) SS-21F Reducing Tee size 1" - 8", SS-50 Concentric Reducer size 1" - 8", SS-50F Concentric Reducer size 1" - 8"

SS grooved fitting, Model(s) SS-21 Reducing Tee size 1 - 8"

Stainless Steel Fittings, Model(s) SS-80 Universal Flange Adapter 2in to 12in

(A) - Product For Use Only in Pipe Applications

t - Product manufactured using NSF 61/ 372 Certified Grade E-pw EPDM Transition Gasket

Last Updated on 2020-12-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"