

VIZM7.EX4688 - Fittings, Rubber Gasketed Certified for Canada

Fittings, Rubber Gasketed Certified for Canada

Aalberts integrated piping systems APAC Inc

295 SEC 3 WANDAN RD
WANDAN TOWNSHIP
PINGTUNG HSIEN, 913 Taiwan

EX4688

Coupling Type Fittings

Model	Groove Type	Pipe	Size In.	Rated Pressure, kPa
7705	Rolled	5	1-1/4, 1-1/2, 2, 2-1/2, 3	1210
7705	Rolled	MODULE-FLOW	1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	2070
7705	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
7705	Rolled	10 (0.188 in.)	10	1210
7705	Rolled, Cut	30 (0.330 in.)	12	1210
7705	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
7705	Rolled, Cut	40	10, 12	1730
7705	Rolled, Cut	BS1387(M)	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	2070
7705	Rolled	DF, XL, XL-II	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
7705	Rolled	EF	1-1/2, 2, 2-1/2, 3	1210
7705	Rolled	EL	1-1/4, 1-1/2, 2	2070
7706	Rolled	10	2x1-1/2; 2-1/2x2; 3x2, 2-1/2; 4x2, 2-1/2, 3; 6x3, 4; 8x6	2070
7706	Rolled, Cut	40	2x1-1/2; 2-1/2x2; 3x2, 2-1/2; 4x2, 2-1/2, 3; 6x3, 4; 8x6	2070
7706	Rolled, Cut	BS1387(M)	3.0 ODx2, 3; 4x2-1/2, 3; 6x4	2070
7707	Rolled	10	3/4, 1, 1-1/4	3450
7707	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	3100
7707	Rolled	10 (0.188 in.)	10, 12	2070
7707	Rolled, Cut	40	10, 12	2070
7707	Rolled, Cut	20 (0.375 in.)	18, 20, 24	1730

Feedback

7707	Rolled, Cut	30 (0.375 in.)	14, 16	2070
7707	Rolled	40	3/4, 1, 1-1/4, 2, 2-1/2, 3, 4, 5, 6, 8	3450
7707	Rolled	BS1387(M)	2-1/2, 5, 6	3450
7707	Rolled	DF	1-1/2, 4	3100
7771	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	2070
7771	Rolled	10	10, 12	1210
7771	Rolled, Cut	20 (0.375 in.)	18, 20	2070
7771	Rolled, Cut	20 (0.375 in.)	22, 24	1730
7771	Rolled, Cut	30 (0.375 in.)	14, 16	2070
7771	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	2070
7771	Rolled, Cut	40	10, 12	1210
7771	Rolled, Cut	BS1387(M)	2, 2-1/2, 3, 4, 5, 6	2070
K-9	Rolled	5	1-1/4, 2, 2-1/2, 3	1210
K-9	Rolled	MODULE-FLOW	1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	2070
K-9	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
K-9	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
K-9	Rolled, Cut	BS1387(M)	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 3.0 OD, 6.5 OD	2070
K-9	Rolled	DF	2, 2-1/2, 3, 4	1210
K-9	Rolled	EL	1-1/4, 2	2070
K-9	Rolled, Cut	ET40	2	2070
K-9	Rolled	XL, XL-II	2, 2-1/2, 3	1210
R20	Rolled	5	2	1210
R20	Rolled	10	2, 3, 4	2070
R20	Rolled, Cut	40	2, 3, 4	2070
R20	Rolled, Cut	BS1387(M)	2, 2-1/2, 3, 4, 5, 6	2070
R20	Rolled	DF	2, 3, 4	2070
R20	Rolled, Cut	EL	2	2070
SS-7	Rolled	10S, 40S	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
SS-7	Rolled	10S, 40S	76.1 mm, 139.7 mm, 165.1 mm	2070
SS-8	Rolled	10S, 40S	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	2070
SS-8	Rolled	10S, 40S	6	1720

SS-8	Rolled, Cut	40S	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	2070
SS-8	Rolled, Cut	40S	6	1720
Z05	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6, 8	2420
Z05	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2420
Z05	Rolled	5	1-1/4, 1-1/2, 2	1210
Z05	Rolled	BLT	1-1/4, 1-1/2, 2	2070
Z05	Rolled	DF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
Z05	Rolled	EF	1-1/4, 1-1/2, 2, 2-1/2, 3	1210
Z05	Rolled	EL	1-1/4, 1-1/2, 2	2070
Z05	Rolled	EZF	3, 4	2070
Z05	Rolled	EZF	6	1210
Z05	Rolled	MF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
Z05	Rolled	MLT, WLS	1-1/4, 1-1/2, 2	2070
Z05	Rolled	MT	1-1/4, 2	2070
Z05	Rolled	XL	1-1/4, 1-1/2, 2	2070
Z05	Rolled	BS1387(M)	1-1/4, 1-1/2, 2, 3, 4	2420
Z05	Rolled	BS1387(M)	76.1 mm	2070
Z07	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	3460
Z07	Rolled	10	5, 6, 8	2760
Z07	Rolled	10	10	2420
Z07	Rolled/Cut	20	12	2420
Z07	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	3460
Z07	Rolled, Cut	40	5, 6, 8	2760
Z07	Rolled, Cut	40	10, 12	2420
Z07	Rolled	5	1-1/4, 1-1/2, 2	1210
Z07	Rolled	DF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
Z07	Rolled	EF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
Z07	Rolled	EL	1-1/4, 1-1/2, 2	2070
Z07	Rolled	EZF	3, 4	2070
Z07	Rolled	EZF	6	1210
Z07	Rolled	MF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070

Z07	Rolled	MLT, WLS	1-1/4, 1-1/2, 2	2070
Z07N	Rolled, Cut	STD	14, 16	1210
F09	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2520
F09	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2520
F09	Rolled	EF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
F09	Rolled	MF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
F09	Rolled	FF	1-1/2, 2, 2-1/2, 3, 4	2070

Flange Adapter Type Fittings

Model	Groove Type	Pipe	Size In.	Rated Pressure, kPa
7041	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	1210
7041	Rolled	10 (0.188 in.)	10	1210
7041	Rolled, Cut	30 (0.330 in.)	12	1210
7041	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	1210
7041	Rolled, Cut	BS1387(M)	3.0 O.D., 4, 5	1210
7043	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	2070
7043	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	2070
C341	Rolled	Type K, Type L	2, 2-1/2, 3, 4, 5, 6	1380
SS-41	Rolled	10S	2, 2-1/2, 3, 4, 5, 6	1210

Side Outlet Type Fittings

Model	Outlet Type	Pipe	Size In.	Rated Pressure, kPa
723	Threaded	10, 40, DF	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1	2070
723	Threaded	EF	1-1/2x1; 2x1	2070
723	Threaded	BS1387(M), XL, XL-II	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1	1210
7721	Threaded	10, 40, BS1387(M)	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2, 3; 6x1-1/4, 1-1/2, 2, 2-1/2, 3, 4; 8x2, 2-1/2, 3, 4	2070
7722	Grooved	10, 40, BS1387(M)	3x1-1/2, 2; 4x1-1/2, 2, 2-1/2, 3; 6x1-1/2, 2, 2-1/2, 3, 4; 8x2, 2-1/2, 3, 4	2070

C-7G	Grooved	10, 40	2x1; 2-1/2x1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2; 4x1-1/2, 2; 6 x 1-1/2, 2	2070
C-7	Threaded	10, 40	1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1; 3x3/4, 1; 4x3/4, 1; 6x1, 1-1/4, 1-1/2	2070
SS-723	Threaded	10S, 40S	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1	2070
M21	Thread	10, 40, EZF	4x3; 6x3, 4	1210
M21	Thread	MF	4x3; 6x3;	1210
M21	Thread	FF, DF	4x3	1210
M21	Thread	BS1387(M)	6x3, 4	1210
M21	Thread	10, 40	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2	2070
M21	Thread	40	5x 2, 2-1/2, 3	2070
M21	Thread	MF	2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2	2070
M21	Thread	EZT	2x1/2, 3/4, 1, 1-1/4, 1-1/2	2070
M21	Thread	FF	2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	2070
M21	Thread	DF	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2	2070
M21	Thread	DF	4x2-1/2	1380
M21	Thread	EF	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	2070
M21	Thread	EZF	3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x 1-1/4, 1-1/2, 2, 2-1/2	2070
M21	Thread	BS1387(M)	2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 5x2, 2-1/2, 3; 6x1-1/4, 1-1/2, 2, 2-1/2	2070
M22	Grooved	10, 40, EZF	4x3;6x3, 4	1210
M22	Grooved	MF	4x3; 6x3	1210
M22	Grooved	FF	4x3	1210
M22	Grooved	BS1387(M)	6x3, 4	1210
M22	Grooved	10, 40	2x1, 1-1/4; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm; 6x1-1/4, 1-1/2, 2, 2-1/2	2070
M22	Grooved	40	5x2, 2-1/2, 76.1 mm, 3	2070

M22	Grooved	MF	2x1; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2	2070
M22	Grooved	FF	2x1; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2	2070
M22	Grooved	DF	2x1, 1-1/4, 1-1/2; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1	2070
M22	Grooved	EF	2x1, 1-1/4, 1-1/2; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2	2070
M22	Grooved	EZF	3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2; 6x 1-1/4, 1-1/2, 2, 2-1/2	2070
M22	Grooved	BS1387(M)	2-1/2x1, 1-1/4, 1-1/2; 4x2-1/2, 76.1 mm; 5x2, 2-1/2, 76.1 mm, 3; 165.1 mmx1-1/4, 1-1/2, 2, 76.1 mm	2070
M21A	Threaded	10, 40	4 x 3; 6 x 3, 4; 8 x 2, 2-1/2, 3, 4	2070
M21A	Threaded	EN10255 (M)	114.3mm x 88.9mm; 165.1mm x 88.9mm, 114.3mm	2070
M22A	Grooved	10, 40	4 x 3; 6 x 3, 4; 8 x 2, 2-1/2, 3, 4	2070
M22A	Grooved	EN10255 (M)	114.3mm x 88.9mm; 165.1mm x 88.9mm, 114.3mm	2070

Models 7705, 7707, 7771, K-9, SS-7, Z-05 and Z07 incorporating Lube-E (Pre-lubricated) gasket are suitable for use in dry pipe systems for temperatures to -40°C.

Models 7705, 7707, 7771, K-9, Z05 and Z07 in following descriptions incorporating Lube-E (Powder Coated) gasket are suitable for use in dry pipe systems for temperatures to -40°C.

Model 7705: from 1 to 12 in. sizes

Model 7707: from 3/4 to 8 in. sizes

Model 7771: from 2 to 12 in. sizes

Model K-9: from 1-1/4 to 8 in. sizes

Model Z05: from 1-1/4 to 8 in. sizes

Model Z07: from 1-1/4 to 12 in. sizes

Model F09 incorporating GapSeal gasket suitable for use in dry pipe systems for temperatures to -40°C.

Models C341 and SS-7 incorporating Lube-E gasket are also suitable for use in dry pipe systems for temperatures to -40°C.

Models 723 and SS-723 in the 1/2 and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Model 7721 and C-7 in the 1/2, 3/4, and 1 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models 723 C-7G, C-7, and SS-723 the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Model M21 in the 1/2 and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models M21, M22, M21A and M22A in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

5 refers to Listed Schedule 5 steel pipe manufactured by Allied Tube & Conduit Corp.

10 refers to Schedule 10 steel pipe.

20 refers to Schedule 20 steel pipe.

30 refers to Schedule 30 steel pipe.

40 refers to Schedule 40 steel pipe.

10S refers to Schedule 10 stainless steel pipe manufactured in accordance with ASTM A312.

40S refers to Schedule 40 stainless steel pipe manufactured in accordance with ASTM A312.

Type K refers to Type K copper pipe manufactured to ASTM B88.

Type L refers to Type L copper pipe manufactured to ASTM B88.

BS1387(M) refers to British Standard Medium steel pipe.

EN10255 (M) refers to EN 10255 Medium steel pipe.

BLT refers to Listed BLT steel pipe manufactured by Allied Tube & Conduit Corp

DF refers to Listed DYNA-FLOW steel pipe manufactured by Allied Tube & Conduit Corp.

EF refers to Listed EDDY FLOW steel pipe manufactured by Bull Moose Tube Co.

EL refers to Listed EDDYLITE steel pipe manufactured by Bull Moose Tube Co.

ET40 refers to Listed Eddythread 40 steel pipe manufactured by Bull Moose Tube Co.

EZF refers to Listed E-Z- Flow steel pipe manufactured by Northwest Pipe Co

MF or MFGF refers to Listed Mega-Flow and Mega-Flow-GF steel pipe manufactured by Wheatland Tube Co Wh Div

MLT refers to Listed MLT and GL steel pipe manufactured by Wheatland Tube Co Wh Div

MT refers to Listed Mega-Thread and Mega-Thread-GT steel pipe manufactured by Wheatland Tube Co Wh Div

WLS refers to Listed WLST steel pipe manufactured by Wheatland Tube Co Wh Div

XL, XL-II refers to Listed XL, XL-II steel pipe manufactured by Allied Tube & Conduit Corp.

AWWA C151 refers to ductile iron pipe constructed in accordance with ANSI/AWWA C151/A21.51 Class 54

EZT refers to Listed EZ-Thread steel pipe manufactured by Youngstown Tube Co

FF refers to Listed Fire-Flo steel pipe manufactured by Youngstown Tube Co

MODULE-FLOW refers to Listed MODULE-FLOW steel pipe manufactured by Josh Global Corp.

STD refers to STD weight class steel pipe manufactured in accordance with ASTM A53.

Trademark and/or Tradename:  , **SHURJOINT** , "SJ", "SHURJOINT"

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

